



Contact Rating

- Nominal Load(Resistive Load $\cos \phi = 1$)
Contact Capacity
BPMF- LM.....16A at 240VAC
- Max. Allowable Current
BPMF- LM.....16A
- Max. Allowable Voltage
BPMF- LM.....AC240V
- Max. Allowable Power Force
BPMF- LM.....3,840VA
- Contact Material..... Ag Alloy
- Contact Form..... SPDT

Performance (at Initial Value)

- Contact Resistance..... $\leq 50m\Omega$ at 6VDC/1A
- Operate Time.....10ms. Max
- Release Time..... 5ms. Max
- Dielectric Strength:
Between Coil & Contact.....5,000VAC at 50/60 Hz
for one minute
Between Contacts.....1,000VAC at 50/60 Hz
for one minute
- Surge Resistance.....10,000V (between Coil
& Contact 1.2x50 μ s)

Main Feature

1. Small size (29x12.6x24.5 in mm) produces a switching capacity up to 16A for high density P.C.Board mounting technique.
2. The contact form construction is 1a
3. The Surge Resistance of BPMF series is 10,000V
4. Sealing Construction (Free from dust and solder flux):
BPMF-S: Flow Solder Type.
5. The selection of plastic insulation material is designed for high temperature and provides better chemical solution performance.

Application

Air Conditioning, Fridge, Washing Machine, etc Household Appliances

- Insulation Resistance.....100 Mega Ω Min. at
500VDC
- Max. On/Off Switching:
Electrical.....30 Ops per minute
Mechanical.....300 Ops per minute
- Temperature Range..... - 30~70°C
- Humidity Range.....45~85% RH
- Coil Temperature Rise..... 35°C Maximum
- Vibration:
Endurance.....10 to 55 Hz dual
amplitude width 1.5mm
Error Operation.....10 to 55 Hz dual
amplitude width 1.5mm
- Shock:
Endurance..... 981m/s² Min
Error Operation..... 98.1m/s² Min
- Life Expectancy:
Electrical.....10⁵ Operations at
Rated Resistive
load
Mechanical.....10⁷ Operations at
No load condition
- Weight.....about 15g

Safety Standard & Its File Number

- UL.....申请中

Coil Specification (at 20 °C)

Coil Sensitivity	Nominal Voltage (VDC)	Nominal Current (mA)	Coil Resistance ($\Omega \pm 8\%$)	Power Consumption (W)	Pull-In Voltage (VDC)	Drop-Out Voltage (VDC)	Maximum Allowable Voltage (VDC)
BPMF-LM	3	176.5	17	Abt. 0.54	75% Maximum	10% Minimum	130%
	5	108.7	46				
	6	89.6	67				
	9	60	150				
	12	44.4	270				
	24	21.8	1100				
	48	11.2	4270				

Ordering Information

BPMF	-	S	-	1	12	L	M			
									Contact Form:	M: Oneo form A
									Coil Type:	L: Standard DC Coil
									Coil Voltage:	05: 5V, 06: 6V, 09: 9V, 12: 12V, 24: 24V, 48: 48V,
									Number of Pole:	1: One Pole
									Type of Sealing:	S: How Solder Type
									Type:	BPMF

Classification

Model	BPMF
Coil Sensitivity	Standard DC Coil 1A
Flow Solder Type	BPMF -S-1□□LM

Dimension

